

This Is An Original Product From Fulham Co., Inc

Description: 350 mA, 50W Constant Current LED Driver. 3 Independent output channels. Voltage input range of 100-240V.


This Driver Will Operate The Following LED Modules.

Any LED module designed to accept constant current input of 350mA and a voltage of 18-56VDC.


ELECTRICAL DATA

INPUT VOLTAGE	100-240 ± 10%, 50/60Hz
INPUT CURRENT (MAX)	0.65A @ 120VAC
POWER FACTOR	> 0.90
THD	< 20% @ Full load
EFFICIENCY	>82% @ 120V, >84% @ 240V
CONSTANT CURRENT, VOLTAGE OR POWER	Constant Current
OUTPUT CURRENT	0.350A / Channel
OUTPUT VOLTAGE	18~56 / Channel
OUTPUT WATTAGE	18.5W (Max) / Channel
NUMBER OF OUTPUT CHANNELS	3
EMI	FCC Part 15, Class A
SURGE PROTECTION	Yes
CURRENT PROTECTION	Yes
OUTPUT SHORT CIRCUIT PROTECTION	Yes
OUTPUT OPEN CIRCUIT PROTECTION	Yes
OUTPUT TO GROUND SHORT PROTECTION	Yes
OVERLOAD PROTECTION	Yes
MAX CASE HOT SPOT TEMPERATURE	75°C
MIN OPERATING TEMPERATURE	-30°C
MAX OPERATING TEMPERATURE	40°C
SERVICE LIFE	50,000 Hours
APPROVALS CLASS	UR Class 2, cUR, CE, Damp location

MECHANICAL DATA



WIRING DIAGRAMS



NOTE : This driver case must be grounded