

Clearv^oyant™

LED SYSTEM₄



PN Canopy	PN Shelf	PN Specialty	Len (in.)	CCT (K)	Output	Flux (lm)	U(VAC)	I (A)	P (W)	Effic (lpw)
P106005C	---	315118	60	4000	HO	2,100	120	0.15	18.5	114
P105994K	---	315119	60	3500	HO	2,100	120	0.15	18.5	114
P105983B	---	315032	60	3000	HO	2,100	120	0.15	18.5	114
P106010B	P105977E	315131	60	4000	SO	900	120	0.06	7.5	120
P105999K	P105969B	315120	60	3500	SO	900	120	0.06	7.5	120
P105988B	P105960M	315109	60	3000	SO	900	120	0.06	7.5	120
P106003G	---	315130	48	4000	HO	1,700	120	0.12	14.9	114
P105992C	---	315108	48	3500	HO	1,700	120	0.12	14.9	114
P105981F	---	315033	48	3000	HO	1,700	120	0.12	14.9	114
P106009E	P105975K	315129	48	4000	SO	700	120	0.05	5.9	119
P105998A	P105967F	315107	48	3500	SO	700	120	0.05	5.9	119
P105987D	P105958E	315034	48	3000	SO	700	120	0.05	5.9	119
P106002K	---	315128	36	4000	HO	1,350	120	0.10	11.9	114
P105991E	---	315117	36	3500	HO	1,350	120	0.10	11.9	114
P105980H	---	315106	36	3000	HO	1,350	120	0.10	11.9	114
P106008G	P105974A	315127	36	4000	SO	550	120	0.04	4.7	117
P105997C	P105966H	315116	36	3500	SO	550	120	0.04	4.7	117
P105986F	P105957G	315105	36	3000	SO	550	120	0.04	4.7	117

Color Quality

- Ra 93
- R9 67
- R9-12 avg. 85

Remote Class 2 Driver

- 120-277 VAC input
- 24 VDC output
- 50/60 Hz

Reliability

- 60,000 hour L85
- 5-year limited warranty