

G24 and GX24 Flush Mount Horizontal Lamp Axis

APPLICATION and PERFORMANCE SPECIFICATION

Description: Lampholders for G24 and GX24 compact fluorescent lamps.

- Body: Casing - PBT GF
- Quick connect terminals: 18 AWG Solid and Stranded
- 660W/600V
- UL Temperature Rating T120

| Type | Ref. # | Base | Lamp | Weight (g) | Packing Unit |
|-------|--------|----------------|----------------|------------|--------------|
| 71701 | 527790 | G24d-1/GX24d-1 | 8, 10, 13 / 13 | 13.2 | 500 |
| 71702 | 527791 | G24d-2/GX24d-2 | 18 / 18 | 13.2 | 500 |
| 71703 | 527792 | G24d-3/GX24d-3 | 26 / 26 | 13.2 | 500 |
| 71711 | 527794 | G24q-1/GX24q-1 | 10, 13 / 13 | 15.2 | 500 |
| 71712 | 527795 | G24q-2/GX24q-2 | 18 / 18 | 15.2 | 500 |
| 71713 | 527796 | G24q-3/GX24q-3 | 26 / 26, 32 | 15.2 | 500 |
| 71719 | 527800 | G24q-3/-4* | 26, 32 / 42 | 15.2 | 500 |
| 71714 | 527797 | G24q-4 | 42 | 15.2 | 500 |
| 71715 | 527798 | G24q-5 | 57 | 15.8 | 500 |
| 71716 | 527799 | G24q-6 | 70 | 15.8 | 500 |

* May only be used in luminaires that are operated with electronic ballasts that have been certified according to the applicable standards and that cover the luminaire performance range of 26, 32, and 42W.

Physical Parameters

- Base mounting holes for self-tapping #8 screws
- Base oblong holes for #8 screws (M4)
- Rear mounting holes for self-tapping #8 screws and self-tapping #8 screws
- Front mounting holes for #4 screws (M3)
- Please see drawings for dimensions

Safety:

- cUL-US listed - Indoor Use (E110363)
- VDE/ENEC Approved



Performance:

- Meets ANSI Standard C81.62-2009
- Meets IEC Standard 60400
- Lampholders meet IP20 standard

Warranty:

Universal Lighting Technologies warrants to the purchaser that each lampholder will be free from defects in material or workmanship for a period of 3 years from date of manufacture when properly installed and under normal conditions of use. Call **1-800-BALLASTx800** for technical assistance.

